



MicroNIR™ PAT-U Spectrometer

A fit-for-purpose near infrared (NIR) analyzer for quality-by-design (QbD) manufacturing

Viavi Solutions® continues to drive spectrometer innovation with the new MicroNIR PAT-U process spectrometer. It is a rugged, scalable, next-generation system for real-time process monitoring in food and pharmaceutical process analytical technology (PAT) applications. With proven Viavi linear variable filter (LVF) technology, the PAT-U has the smallest form factor on the market in a fit-for-purpose design. This makes it ideal for use with processing equipment of all sizes, with the performance and stability to enable truly efficient manufacturing.

The easy-to-use MicroNIR PAT-U was designed for today's demanding GMP-regulated environments yet requires minimal system maintenance. It has no moving components or expensive fiber optic cables, enabling superior instrument stability and performance in harsh process environments. Its stainless steel exterior resists dust and water to IP65 standards and cleans easily.



Key Features

- Non-invasive, real-time NIR analysis
- Washable, IP67 rated enclosure
- USB communication
- Compact for easy integration

Applications

Pharmaceutical Manufacturing

- Fluid bed drying
- Granulation
- Content uniformity

Food and Feed Manufacturing

- Moisture content
- Nutritional assay
- Protein
- Fat


Industrial Processing

- Reaction monitoring
- Polymers
- Petrochemicals

MicroNIR Software

The software suite allows for deployment flexibility from process/product development to manufacturing environments and features audit trails, comprehensive user management, encrypted secure data storage, and many other capabilities required for regulated GMP environments.

- The instrument control software enables easy data acquisition, method investigation, real-time analysis, user management, method development, and instrument qualification per USP 1119 criteria.
- Viavi Unscrambler® X Lite regression and classification software provides a complete set of chemometric tools for calibration model development and data investigation.
- The MicroNIR Process software is designed for easy process monitoring of different process methods from different MicroNIR spectrometers. Process Engineers can easily view collected data and trend results in real-time with simultaneous output of key process data to the plant control system.



Mounting and Process Integration

The MicroNIR PAT-U has been designed with maximum flexibility in mind to meet the many different criteria for process integration. It integrates into a process with three different mounts:

Standard

This includes a weld in base flange, a 2" sanitary (hygienic) flange mount, a sapphire window, and a retaining ring with O-rings. The base flange is welded into a hole cut in the specific process equipment and then the sanitary flange mount, window, and retaining ring are assembled. The PAT-U with an adjustable collet then secures against the window and a sanitary flange using a standard tri-clover clamp (or C-clamp). All pieces disassemble for easy cleaning and maintenance.

Threaded

This mount lets a user weld a mount into the process equipment and subsequently attach the PAT-U using the threaded tip of the spectrometer. The threaded mount also contains a removable window for easy cleaning and maintenance.



Standard mount

Specifications

Parameter	Specification
Illumination source	Two integrated vacuum tungsten lamps
Bulb life	>40,000 hours
Illumination geometry	Flood illumination/ 0° observer
Input aperture dimensions	2.5 x 3.0 mm
Sample working distance	0 – 15 mm from window
Dispersing element	Linear variable filter
Detector	128-pixel InGaAs photodiode array
Pixel size/pitch	30 µm x 250 µm/50 µm
Wavelength range	950 – 1650 nm (10,526 – 6060 cm ⁻¹)
Pixel-to-pixel interval	6.2 nm for 950 – 1650 nm
Spectral bandwidth (FWHM)	<1.25% of center wavelength (1% typical) (for example, @1000 nm, resolution is <12.5 nm)
Analog-to-digital convertor	16 bit
Dynamic range (Max)	1000:1
Measurement time (typical)	0.25 – 0.5 second
Integration time	10 ms typical, minimum 10 µsec, maximum limited by dark signal
Computer interface	USB 2.0
Spectrometer weight	318 g (11.2 oz) With window collar: 368 g or (13 oz)
Size	45 mm diameter x 69 mm tall
Power	USB powered (<500 mA @5V)
Data format	Encrypted, Unsb, CSV, and SPC output
Operating system	Windows 8.1, 8, and 7
Software available	MicroNIR Pro standard, Unscrambler X Lite, MicroNIR Process
Operating temperature	0 – 40 deg C (non-condensing)
Enclosure	Stainless steel 316: dust and waterproof, sealed and cleanable to IP67 standard
Mounting	Adaptable stainless steel tri-clover mount, screw into welded flange

For more information on this or other products, please contact your local distributor:



Tel. 051 392 391 | e-mail: info@antech.ie | web: www.antech.ie